

Kjeldahl method for determining nitrogen



www.behr-labor.com

Quality made in Germany 

Contents

Kjeldahl method for determining nitrogen

The behr program for determination of nitrogen using the Kjeldahl method _____ 4



behr Kjeldahl block digestion systems _____ 6

Standard Kjeldahl block digestion systems, behr K 8, K 12 und K 20 _____ 6

Micro Kjeldahl block digestion systems, behr K 16, K 24 und K 40 _____ 6

Macro Kjeldahl block digestion systems, behr K 8 B _____ 7

behr Kjeldahl block digestion systems with fully automatic lift _____ 7

Accessories for Kjeldahl block digestion systems _____ 9



Infrared rapid digestion units _____ 10

Infrared digestion compared to block digestion _____ 11

Digestion units _____ 12

Digestion system with temperature control _____ 16

Accessories for behr InKjel _____ 17

behrotest® fully equipped work stations _____ 18

behrosog 3 scrubber _____ 20



behr steam distillers S 1 to S 5 _____ 22

Maintenance set _____ 23

Steam distillers S1 and S2 _____ 24

Steam distillers S3 and S4 _____ 25

Steam distiller S5 _____ 26

Equipping the models _____ 27


Adapter for using different digestion vessels _____ 28

Canister sets and Manual titration station STI _____ 29

behrotest® Dispenser _____ 30

The behr program for the

Kjeldahl method for determining nitrogen



The behr program for the determination of nitrogen using the Kjeldahl method provides the user individually configurable complete solutions for the laboratory.

Digestion units

Kjeldahl block digestion systems

Block digestion systems with high-quality corrosion-resistant block housing made of sheet metal with powder coating. Manual or with automatic lift.

- High-efficiency heating and extraction hood with exhaust collector
- behr single-knob control for particularly easy and fast programming
- Menu navigation in national language
- 10 freely configurable programs à 20 program steps each for block temperature and digestion time
- Applications can be saved

Standard systems

- Digestion vessels with 250 ml volume (8, 12 or 20 sample slots)

Micro-Kjeldahl systems

- Digestion vessels with 100 ml volume (16, 24 or 40 sample slots)

Infrared digestion systems

The digestion units of the behrotest® InKjel series are equipped with efficient quartz glass infrared heating. Apart from the traditional series with energy control, there is a fully equipped series of appliances for temperature-controlled digestion.

The quality and positioning of the behr infrared heaters guarantees the user identical heating phases and digestion temperatures on all sample slots. This also applies to double-rowed arrangement in insert racks for 12 samples.

Direct sample heating by the infrared heaters prevents the agonisingly long heating and cooling times of conventional heating block systems.

The behrotest® InKjel is therefore the ideal rapid digestion system for the determination of nitrogen using the Kjeldahl method and other high-temperature digestion tests.

Scrubber

The two-stage behrosog scrubber – pre-separator plus safety stage – prevents any acid fumes whatsoever from reaching the environment.

Titration stations

The behrotest® STI manual titration station or an automatic titrator ensure reliable, safe and fast titration for completion of the nitrogen determination.

Areas of application

Dairies

Cocoa/drinking chocolate

Meat/sausages

Biogas plants

Preserves/
canned foods

Malt houses

Spirits

Delicatessen

Coffee

Nuts

Wastewater

Feedstuffs

Block digestion systems

behr Kjeldahl block digestion systems

Standard Kjeldahl block digestion systems, behr K 8, K 12 and K 20

Block digestion systems with high-quality corrosion-resistant block housing made of sheet metal with powder coating. With 8, 12 or 20 sample slots for standard Kjeldahl digestion vessels with a volume of 250 ml. High-efficiency heating and extraction hood with exhaust collector.

- behr single-knob control for particularly easy and fast programming.
- Menu navigation in national language.
- 10 freely configurable programs à 20 program steps each for block temperature and digestion time.
- Applications can be saved.
- USB interface.
- The removable inspection door on the insertion rack enables the progress of the digestion to be observed.

Complete systems with digestion vessels, rack and extraction hood.

Standard Kjeldahl block digestion system

| Type | Product description | Art. No. |
|------|---|-----------|
| K 8 | with 8 sample slots, for digestion vessels with a volume of 250 ml | B00632822 |
| K 12 | with 12 sample slots, for digestion vessels with a volume of 250 ml | B00605456 |
| K 20 | with 20 sample slots, for digestion vessels with a volume of 250 ml | B00632831 |



K 12

Micro Kjeldahl block digestion systems, behr K 16, K 24 and K 40

Block digestion systems with high-quality corrosion-resistant block housing made of sheet metal with powder coating. With 16, 24 or 40 sample slots for micro Kjeldahl digestion vessels with a volume of 100 ml. High-efficiency heating and extraction hood with exhaust collector.

- behr single-knob control for particularly easy and fast programming.
- Menu navigation in national language.
- 10 freely configurable programs à 20 program steps each for block temperature and digestion time.
- Applications can be saved.
- USB interface.
- The removable inspection door on the insertion rack enables the progress of the digestion to be observed.

Complete systems with digestion vessels, rack and extraction hood.

Micro Kjeldahl block digestion system

| Type | Product description | Art. No. |
|------|---|-----------|
| K 16 | with 16 sample slots, for digestion vessels with a volume of 100 ml | B00632829 |
| K 24 | with 24 sample slots, for digestion vessels with a volume of 100 ml | B00632828 |
| K 40 | with 40 sample slots, for digestion vessels with a volume of 100 ml | B00632821 |



K 20

Macro-Kjeldahl block digestion systems, behr K 8 B

Block digestion systems with high-quality corrosion-resistant block housing made of sheet metal with powder coating. With 8 sample slots, for macro Kjeldahl digestion vessels with a volume of 400 ml. High-efficiency heating and extraction hood with exhaust collector.

- behr single-knob control for particularly easy and fast programming.
- Menu navigation in national language.
- 10 freely configurable programs à 20 program steps each for block temperature and digestion time.
- Applications can be saved.
- USB interface.
- The removable inspection door on the insertion rack enables the progress of the digestion to be observed.

Complete systems with digestion vessels, rack and extraction hood.

Macro Kjeldahl block digestion system

| Type | Product description | Art. No. |
|-------|--|-----------|
| K 8 B | with 8 sample slots, for digestion vessels with a volume of 400 ml | B00632830 |



K 8 B

Technical data of the behr Kjeldahl block digestion systems

| | K 8 | K 12 | K 16/K 24 | K 20/K 40 |
|-------------------------------------|----------------------|------------------|------------------|-------------------------|
| Voltage | 230 VAC | | | |
| Frequency | 50/60 Hz | | | |
| Power consumption | 1000 W | 1500 W | 1500 W | 2200 W |
| Current consumption | 5 A | 8 A | 8 A | 10 A |
| Weight (incl. vessels) | approx. 28 kg | approx. 30 kg | approx. 30 kg | approx. 34 kg |
| Dimensions in cm (W x D x H) | approx. 42 x 51 x 77 | | | approx. 48 x 51 x 77 |
| Temperature range | 430° | | | |

behr Kjeldahl block digestion systems with fully automatic lift

behr's L series Kjeldahl block digestion systems are equipped with a fully automatic lift. This enables the user to avoid handling the heavy samples unit and the hot chemicals. The software not only controls the sample lift but also the behrosog 3 and therefore enables largely automatic digestion.

At the end of the digestion the lift moves the complete unit upwards, including the rack and extraction hood. Following a freely programmable cooling/ extraction time, it raises the extraction hood and moves it into the end position.

- Temperature profiles and the starting time of the digestion are freely programmable.
- behr single-knob control for particularly easy and fast programming.
- USB interface.
- The removable inspection door on the insertion rack enables the progress of the digestion to be observed.

Available with 230 V~/50-60 Hz.



K 16 L



K 40 L

behr Kjeldahl block digestion systems with fully automatic lift

| Type | Product description | Art. No. |
|--------|---|-----------|
| K 8 L | Kjeldahl block digestion system with fully automatic lift. 8 sample slots, for digestion vessels with a volume of 250 ml | B00632823 |
| K 12 L | Kjeldahl block digestion system with fully automatic lift. 12 sample slots, for digestion vessels with a volume of 250 ml | B00632827 |
| K 16 L | Micro Kjeldahl block digestion system with fully automatic lift. 16 sample slots, for digestion vessels with a volume of 100 ml | B00658059 |
| K 20 L | Kjeldahl block digestion system with fully automatic lift. 20 sample slots, for digestion vessels with a volume of 250 ml | B00632826 |
| K 24 L | Micro Kjeldahl block digestion system with fully automatic lift. 24 sample slots, for digestion vessels with a volume of 100 ml | B00632825 |
| K 40 L | Micro Kjeldahl block digestion system with fully automatic lift. 40 sample slots, for digestion vessels with a volume of 100 ml | B00632824 |

Technical data of the behr Kjeldahl block digestion systems with fully automatic lift

| | K 8 L | K 12L/K 16L/K 24L | K 20L/K 40L |
|-------------------------------------|----------------------|-------------------|----------------------|
| Voltage | 230 VAC | | |
| Frequency | 50/60 Hz | | |
| Power consumption | 1050 W | 1550 W | 2250 W |
| Current consumption | 5 A | 8 A | 10 A |
| Weight (incl. vessels) | approx. 47 kg | approx. 49 kg | approx. 53 kg |
| Dimensions in cm (W x D x H) | approx. 42 x 58 x 77 | | approx. 48 x 58 x 77 |
| Temperature range | 430° | | |

Fully automatic



Accessories for Kjeldahl block digestion systems

Digestion vessels for K blocks

| Type | Product description | Art. No. |
|-------|--|-----------|
| SR 3i | Round bottom digestion vessel, 250 ml | B00217959 |
| SR 4 | Round bottom digestion vessel, 100 ml for micro Kjeldahl | B00217960 |
| SR 5 | Round bottom digestion vessel, 400 ml for K 8 B | B00373170 |



SR 3i

SR 4

SR 5

Good to know:


behrotest® standard digestion vessels have standard dimensions. That means they fit into digestion and distillation units of most brands. Of course, it also means that standard digestion vessels of most brands can be used with behrotest® digestion and distillation units.

Accessories for the behr Kjeldahl digestion

| Type | Product description | Art. No. |
|----------|--|-----------|
| KT 1 | Catalyst tablets (5.0 g K_2SO_4 ; 0.5 g $CuSO_4$), tin with 1000 tablets (CX) | B00217934 |
| KT 1-500 | Catalyst tablets (5.0 g K_2SO_4 ; 0.5 g $CuSO_4$), tin with 500 tablets (CX) | B00727970 |
| KT 2 | Catalyst tablets (5.0 g K_2SO_4 ; 0.15 g $CuSO_4$; 0.15 g TiO_2), tin with 1000 tablets (CT) | B00217935 |
| KT 2-500 | Catalyst tablets (5.0 g K_2SO_4 ; 0.15 g $CuSO_4$; 0.15 g TiO_2), tin with 500 tablets (CT) | B00727971 |
| KT 3 | Catalyst tablets (3.5 g K_2SO_4 ; 0.4 g $CuSO_4$), tin with 1000 tablets (CK) | B00217937 |
| KT 3-500 | Catalyst tablets (3.5 g K_2SO_4 ; 0.4 g $CuSO_4$), tin with 500 tablets (CK) | B00727972 |
| KT 4 | Catalyst tablets (3.5 g K_2SO_4 ; 0,0035 g Se), tin with 1000 tablets (ST) | B00490920 |
| KT 4-500 | Catalyst tablets (3.5 g K_2SO_4 ; 0,0035 g Se), tin with 500 tablets (ST) | B00727973 |
| AFS | Anti-foam tablets, tin with 100 tablets for steam distillation | B00217936 |
| SIST 100 | Boiling stones for the Kjeldahl digestion, contents 100 g | B00217914 |
| WP | Weighing paper, block of 250 sheets, 95 x 110 mm | B00441136 |
| WB 1 | behrotest® Weighing boats for Kjeldahl, 58 x 10 x 10 mm | B00217938 |
| DOS 25 | behrotest® dispenser for metering sulfuric acid, 2.5-25 ml adjustable without bottle | B00661157 |



KT 2



SIST 100

Infrared rapid detection units



behrotest® InKjel






Infrared digestion compared to block digestion

Particularly uniform heating of the samples using side heaters, therefore no zones with different temperatures. Hardly any boiling delays..



Quartz heaters:

- uniform effect along the entire length
- insulated from the housing, no energy loss through heat transfer
- full heat output within 1 minute, no preheating required



Digestion units

The digestion units of the behrotest® InKjel series are equipped with efficient infrared heating. The quality and positioning of the behr infrared heaters guarantees the user identical heating phases and digestion temperatures on all sample slots. This also applies to double-rowed arrangement in insert racks for 12 samples. The digestion tubes hang in the rack and do not touch the bottom of the digester. As a result, the digestion vessels are at less risk of breakage than in an aluminium heating block.

- Direct sample heating by the infrared heaters prevents the agonisingly long heating times of conventional heating block systems.
- You can reach a radiation temperature of 830 °C within one minute and heat up the samples in 10 minutes to their boiling temperature of 410°C.
- High-quality quartz heaters instead of the usual steel tubular heating elements ensure particularly uniform heating of all sample slots.
- behr single-knob control for particularly easy and fast programming.
- Menu navigation in national language.

The behrotest® InKjel is therefore the ideal digestion system for the determination of nitrogen using the Kjeldahl method and other high-temperature digestion tests. With the Kjeldahl digestion method, the temperature is set by the boiling temperature of the sulphuric acid.



InKjel 625 M

InKjel 625 M rapid digestion system with manual energy control for 6 sample slots, 250 ml

Rapid digestion system with manual energy control and direct heating of the samples using high-quality quartz infrared heaters (1500 W).

- 6 glass digestion tubes of 250 ml
- Constant heating of all samples to 410 °C in approx. 10 minutes
- Uniform heating of all sample slots
- Energy savings compared to aluminium block

Complete system with tiered rack, fume removal unit, insert rack and glass digestion tubes.

| Type | Product description | Art. No. |
|--------------|---|-----------|
| InKjel 625 M | Manually controllable infrared digestion system for 6 glass tubes of 250 ml | B00218101 |



InKjel 625 P

InKjel 625 P rapid digestion system with 10 freely configurable programs à 20 program steps each for energy and digestion time for 6 sample slots, 250 ml

Rapid digestion system with 10 freely configurable programs à 20 program steps each for energy and digestion time and direct heating of the samples using high-quality quartz infrared heaters (1500 W).

- 6 glass digestion tubes of 250 ml
- Constant heating of all samples to 410 °C in approx. 10 minutes
- Uniform heating of all sample slots
- Energy savings compared to aluminium block

Complete system with tiered rack, fume removal unit, insert rack and glass digestion tubes.

| Type | Product description | Art. No. |
|--------------|--|-----------|
| InKjel 625 P | Programmable infrared digestion system for 6 glass tubes of 250 ml | B00218105 |

InKjel 1210 M rapid digestion system with manual energy control for 12 sample slots, 100 ml

Rapid digestion system with manual energy control and direct heating of the samples using high-quality quartz infrared heaters (1500 W).

- 12 glass digestion tubes of 100 ml
- Constant heating of all samples to 410 °C in approx. 10 minutes
- Uniform heating of all sample slots
- Energy savings compared to aluminium block

Complete system with tiered rack, fume removal unit, insert rack and glass digestion tubes.

| Type | Product description | Art. No. |
|---------------|--|-----------|
| InKjel 1210 M | Manually controllable infrared digestion system for 12 glass tubes of 100 ml | B00373235 |



InKjel 1210 M

InKjel 1210 P rapid digestion system with 10 freely configurable programs à 20 program steps each for energy and digestion time for 12 sample slots, 100 ml

Rapid digestion system with 10 freely configurable programs à 20 program steps each for energy and digestion time and direct heating of the samples using high-quality quartz infrared heaters (1500 W).

- 12 glass digestion tubes of 100 ml
- Constant heating of all samples to 410 °C in approx. 10 minutes
- Uniform heating of all sample slots
- Energy savings compared to aluminium block

Complete system with tiered rack, fume removal unit, insert rack and glass digestion tubes.

| Type | Product description | Art. No. |
|---------------|---|-----------|
| InKjel 1210 P | Programmable infrared digestion system for 12 glass tubes of 100 ml | B00497540 |



InKjel 1210 P

InKjel 1225 M rapid digestion system with manual energy control for 12 sample slots, 250 ml

Rapid digestion system with manual energy control and direct heating of the samples using high-quality quartz infrared heaters (1500 W).

- 12 glass digestion tubes of 250 ml
- Constant heating of all samples to 410 °C in approx. 10 minutes
- Uniform heating of all sample slots
- Energy savings compared to aluminium block

Complete system with tiered rack, fume removal unit, insert rack and glass digestion tubes.

| Type | Product description | Art. No. |
|---------------|--|-----------|
| InKjel 1225 M | Manually controllable infrared digestion system for 12 glass tubes of 250 ml | B00218103 |



InKjel 1225 M



InKjel 1225 P

InKjel 1225 P rapid digestion system with 10 freely configurable programs à 20 program steps each for energy and digestion time for 12 sample slots, 250 ml

Rapid digestion system with 10 freely configurable programs à 20 program steps each for energy and digestion time and direct heating of the samples using high-quality quartz infrared heaters (1500 W).

- 12 glass digestion tubes of 250 ml
- Constant heating of all samples to 410 °C in approx. 10 minutes
- Uniform heating of all sample slots
- Energy savings compared to aluminium block

Complete system with tiered rack, fume removal unit, insert rack and glass digestion tubes.

| Type | Product description | Art. No. |
|---------------|---|-----------|
| InKjel 1225 P | Programmable infrared digestion system for 12 glass tubes of 250 ml | B00218106 |



InKjel 450 M

InKjel 450 M rapid digestion system with manual energy control for 4 sample slots, 500 ml

Rapid digestion system with manual energy control and direct heating of the samples using high-quality quartz infrared heaters (1500 W).

- 4 glass digestion tubes of 500 ml
- Constant heating of all samples to 410 °C in approx. 10 minutes
- Uniform heating of all sample slots
- Energy savings compared to aluminium block

Complete system with tiered rack, fume removal unit, insert rack and glass digestion tubes.

| Type | Product description | Art. No. |
|--------------|---|-----------|
| InKjel 450 M | Manually controllable infrared digestion system for 4 glass tubes of 500 ml | B00218067 |



InKjel 450 P

InKjel 450 P rapid digestion system with 10 freely configurable programs à 20 program steps each for energy and digestion time for 4 sample slots, 500 ml

Rapid digestion system with 10 freely configurable programs à 20 program steps each for energy and digestion time and direct heating of the samples using high-quality quartz infrared heaters (1500 W).

- 4 glass digestion tubes of 500 ml
- Constant heating of all samples to 410 °C in approx. 10 minutes
- Uniform heating of all sample slots
- Energy savings compared to aluminium block

Complete system with tiered rack, fume removal unit, insert rack and glass digestion tubes.

| Type | Product description | Art. No. |
|--------------|--|-----------|
| InKjel 450 P | Programmable infrared digestion system for 4 glass tubes of 500 ml | B00218107 |

InKjel 475 M rapid digestion system with manual energy control for 4 sample slots, 750 ml

Rapid digestion system with manual energy control and direct heating of the samples using high-quality quartz infrared heaters (1500 W).

- 4 glass digestion tubes of 750 ml
- Constant heating of all samples to 410 °C in approx. 10 minutes
- Uniform heating of all sample slots
- Energy savings compared to aluminium block

Complete system with tiered rack, fume removal unit, insert rack and glass digestion tubes.

| Type | Product description | Art. No. |
|--------------|---|-----------|
| InKjel 475 M | Manually controllable infrared digestion system for 4 glass tubes of 750 ml | B00218068 |



InKjel 475 P rapid digestion system with 10 freely configurable programs à 20 program steps each for energy and digestion time for 4 sample slots, 750 ml

Rapid digestion system with 10 freely configurable programs à 20 program steps each for energy and digestion time and direct heating of the samples using high-quality quartz infrared heaters (1500 W).

- 4 glass digestion tubes of 750 ml
- Constant heating of all samples to 410 °C in approx. 10 minutes
- Uniform heating of all sample slots
- Energy savings compared to aluminium block

Complete system with tiered rack, fume removal unit, insert rack and glass digestion tubes.

| Type | Product description | Art. No. |
|--------------|--|-----------|
| InKjel 475 P | Programmable infrared digestion system for 4 glass tubes of 750 ml | B00218108 |



InKjel 475 P

Technical data for digestion systems

| | InKjel M | InKjel P |
|-------------------------------------|---|---------------------------------|
| Voltage | 230 VAC | |
| Frequency | 50/60 Hz | |
| Power consumption | 1500 W | 1500 W |
| Current consumption | 8 A | 8 A |
| Weight (incl. vessels) | approx. 20 kg | approx. 20 kg |
| Dimensions in cm (W x D x H) | approx. 54 x 44 x 75 | approx. 54 x 44 x 75 |
| Energy setting range | 0... 100%, continuously variable, manually adjustable | 0... 100%, in steps of 1 % |
| Time setting range | – | 0... 199 min, in steps of 1 min |
| Programs | – | 10 |

Rapid infrared digestion systems

behrotest® InKjel TC



Rapid infrared digestion systems with temperature control

behrotest InKjel TC rapid infrared devices with temperature control combine the advantages of infrared digestion and block digestion in one unit: Their fast infrared digestion at controlled temperatures enables an extremely high sample throughput.

With the programmable models of the InKjel TCP line the analyst has the choice from 10 freely configurable programs à 20 program steps each for temperature and digestion time.

You can reach a radiation temperature of 830 °C within one minute and heat up the samples in 10 minutes to their boiling temperature of 410°C. High-quality quartz heaters instead of the usual steel tubular heating elements ensure particularly uniform heating of all sample slots.



InKjel 1225 TCP

Digestion systems with temperature control

| Type | Product description | Art. No. |
|-----------------|---|-----------|
| InKjel 625 TCP | Programmable rapid infrared digestion system for 6 reaction vessels with 250 ml volume. Temperature control. | B00636206 |
| InKjel 1210 TCP | Programmable rapid infrared digestion system for 10 reaction vessels with 100 ml volume. Temperature control. | B00636207 |
| InKjel 1225 TCP | Programmable rapid infrared digestion system for 12 reaction vessels with 250 ml volume. Temperature control. | B00636208 |
| InKjel 450 TCP | Programmable rapid infrared digestion system for 4 reaction vessels with 500 ml volume. Temperature control. | B00636209 |
| InKjel 475 TCP | Programmable rapid infrared digestion system for 4 reaction vessels with 750 ml volume. Temperature control. | B00636210 |

Accessories for behr InKjel

Accessories for behr InKjel



AE 6



| Type | Product description | Art. No. |
|-----------|---|-----------|
| AE 4 | Fume removal equipment for InKjel 450 and InKjel 475 (M and P) | B00218088 |
| AE 6 | Fume removal equipment for InKjel 625 (M and P) | B00218089 |
| AE 12/100 | Fume removal equipment for InKjel 1210 (M and P) | B00218070 |
| AE 12 | Fume removal equipment for InKjel 1225 (M and P) | B00218090 |
| EG 12/100 | Insert rack for 12 digestion vessels of 100 ml in the InKjel 1210 (M and P) | B00218069 |
| EG 6 | Insert rack for 6 digestion vessels of 250 ml in the InKjel 625 (M and P) | B00218086 |
| EG 12 | Insert rack for 12 digestion vessels of 250 ml in the InKjel 1225 (M and P) | B00218087 |
| EG 4/500 | Insert rack for 4 digestion vessels of 500 ml in the InKjel 450 (M and P) | B00218085 |
| EG 4/750 | Insert rack for 4 digestion vessels of 750 ml in the InKjel 475 (M and P) | B00218080 |



SR 3i

SR 4

KJ 500

KJ 750

Digestion vessels for InKjel

| Type | Product description | Art. No. |
|--------|--|-----------|
| SR 3i | Round bottom digestion vessel, 250 ml | B00217959 |
| SR 4 | Round bottom digestion vessel, 100 ml for micro Kjeldahl | B00217960 |
| KJ 500 | Round bottom digestion vessel, 500 ml | B00218195 |
| KJ 750 | Round bottom digestion vessel, 750 ml for InKjel | B00218218 |

behrotest[®] fully equipped work stations

for nitrogen determination according to Kjeldahl

Based on our block or infrared digestion systems, we have put together various full configurations for users with diverse requirements.

Basic system for Kjeldahl digestion and distillation:

Type ASB work stations

- Digestion units for 6 samples (Infrared: InKjel 625 M) or 8 samples (block digestion: K 8) simultaneous.
- Standard digestion in vessels à 250 ml.
- Extraction system with water jet pump and neutralisation phase (SIMVAC).
- Steam distiller (S1).

| Type | | Art. No. |
|--------|--|-----------|
| ASB-IR | Infrared with energy control | B00637679 |
| ASB-K | Block digestion with temperature control | B00637682 |

Full system for the determination of nitrogen incl. titration:

Type ASM work stations

- Programmable digestion units for 12 samples (Infrared: InKjel 1225 P, block digestion: K 12) simultaneous.
- Standard digestion in vessels à 250 ml.
- Scrubber (behrosog 3).
- Steam distiller (S 3).
- Titration station (STI).

| Type | | Art. No. |
|--------|--|-----------|
| ASM-IR | Infrared with energy control | B00637680 |
| ASM-K | Block digestion with temperature control | B00637683 |

Full system for the determination of nitrogen:

Type ASE work stations

- Programmable digestion units for 12 samples (Infrared: InKjel 1225 TCP with temperature control) or 20 samples (block digestion: K 20) simultaneous.
- Standard digestion in vessels à 250 ml.
- Scrubber (behrosog 3) with additional cooling system (ACS).
- Steam distiller (S 5).
- Connection option for external titrator (e.g. TB 2).

| Type | | Art. No. |
|--------|--|-----------|
| ASE-IR | Infrared with temperature control | B00637681 |
| ASE-K | Block digestion with temperature control | B00637684 |
| TB 2 | Titration module for connection to the S 5 steam distilling apparatus, with Kjeldahl method and evaluation. Printer upon request | B00645403 |



ASB-IR




ASM-IR



ASE-IR

behrosog 3 Scrubber

Scrubber



Scrubber

The two-stage behrosog process extraction system (scrubber) – pre-separator plus safety stage – prevents any acid fumes whatsoever from reaching the environment. Compact process extraction system for extracting and neutralising aggressive acid fumes, especially from the Kjeldahl digestion method for nitrogen determination. An upstream two-stage pre-separator washes out the toxic substances. The process extraction system is equipped with a vacuum pump 40 l/min. There is no need to connect to the water supply.

- Efficient running costs
- Continuously variable intake flow
- Both cleaning stages (condensation and neutralisation stage) prevent the emission of toxic substances into the environment

Optionally, the additional cooling system for the behrosog 3 ACS can be connected to the system, consisting of stand, bottles and cooler.

Scrubber

| Type | Product description | Art. No. |
|------------|---|-----------|
| behrosog 3 | Scrubber with suction pump (40 l/min), cooling stage, neutralisation stage and drip catcher | B00217925 |
| ACS | Additional cooling system for behrosog 3, for samples with high water content | B00217927 |
| | Bromothymol blue Indicator | B00682430 |

Technical data for the behrosog 3 scrubber

| | |
|-------------------------------------|-------------------------------------|
| Voltage | 230 VAC |
| Frequency | 50/60 Hz |
| Power consumption | 80 W |
| Weight | approx. 18 kg |
| Dimensions in cm (W x D x H) | approx. 38 x 34 x 40 |
| Pump delivery rate | max. 40 l/ min without backpressure |

SIMVAC

Suction device with water jet pump and neutralisation bottle incl. hose and frame. Without fittings!

| Type | Article description | Art. No. |
|--------|-------------------------------------|-----------|
| SIMVAC | water jet pump based neutralisation | B00217922 |

| Air suction | Water consumption |
|-------------|-------------------|
| 20 l/min | 13 l/min |
| 28 l/min | 16 l/min |



behrosog 3



behrosog 3
with ACS



SIMVAC

behr steam distillers S 1 to S 5

Customised features



Exemplary safety for the steam distillation

behr steam distillers are not only efficient and reliable partners in everyday laboratory life. An important issue during the development and design of the equipment was also the safety of users.

Therefore, all steam distillers have:

- a protection switch as master switch, which automatically trips in the event of overload and short-circuit
- a mechanical overpressure safety valve to prevent excessive pressure in the steam generator
- vessel monitoring (distillation is not possible until a vessel has been inserted)
- a door contact switch, which automatically switches off the distiller if the door is open
- a resettable excess temperature thermostat (in the event of lack of water in the steam generator)
- cooling circuit monitoring by means of pressure switches
- temperature-controlled steam heating phase and pressure control via solenoid valve

Steam distillers

behr S series steam distillers are the optimum addition to the behr Kjeldahl digestion system. Depending on the requirements, the user can choose between five automatic steam distillers. These have identical basic designs, however, their ease of use and degree of automation differ. The top of the range unit, the behr S 5, is prepared for work with an external titrator.

Maintenance set for behrotest® steam distillers

The set comes with all the necessary spare parts for the working area as well as for the interior of the behrotest® steam distillers.

The maintenance set included are exactly those

- screw caps,
- seals,
- tubes and
- valves


which are prone to wear out during everyday use in the laboratory.



| Type | Art. No. |
|----------------------------|-----------|
| behrotest® maintenance set | B00606938 |

behrotest®
maintenance set

Maintenance friendly design



Important tubes, valves and pumps etc. for service and maintenance work are all freely accessible.

User friendly design:

doors at the rear can be opened simply without tools and give access for routine maintenance work.



S 1

Steam distiller S 1 with automatic addition of NaOH

- Exemplary safety and reliability
- Robust and insensitive housing made of polyurethane
- Distillation time approx. 3 min per sample
- Detection limit 0.1 mg N
- Retrieval rate > 99.5%
- Reproducibility $\pm 1\%$
- Adjustable steam output (10% - 100%)
- Particularly easy, menu-driven operation using a single control (behr single-knob control)
- Programmable reaction time
- Programmable distillation time
- USB interface
- Level monitoring for the canister set
- Practical quick-release clamping device, which the user can also easily operate with their left hand

S 1

| Type | Product description | Art. No. |
|-----------|--|-----------|
| S 1 | Steam distiller, semi-automated | B00218025 |
| KAS 20 | Canister set for S 1 and S 2, consisting of 2 canisters à 20 l, incl. float switches | B00218041 |
| KAS 20/10 | Canister set for S 1 and S 2, consisting of 2 canisters à 10 l, incl. float switches | B00704640 |



S 2

Steam distiller S 2 with automatic addition of NaOH and H₂O

- Exemplary safety and reliability
- Robust and insensitive housing made of polyurethane
- Distillation time approx. 3 min per sample
- Detection limit 0.1 mg N
- Retrieval rate > 99.5%
- Reproducibility $\pm 1\%$
- Adjustable steam output (10% - 100%)
- Particularly easy, menu-driven operation using a single control (behr single-knob control)
- Programmable reaction time
- Programmable distillation time
- USB interface
- Level monitoring for the canister set
- Practical quick-release clamping device, which the user can also easily operate with their left hand

S 2

| Type | Product description | Art. No. |
|-----------|--|-----------|
| S 2 | Steam distiller, semi-automated | B00233702 |
| KAS 20 | Canister set for S 1 and S 2, consisting of 2 canisters à 20 l, incl. float switches | B00218041 |
| KAS 20/10 | Canister set for S 1 and S 2, consisting of 2 canisters à 10 l, incl. float switches | B00704640 |

Steam distiller S 3 with automatic addition of NaOH and H₂O with automatic extraction of the sample residues and with 10 programs

- Exemplary safety and reliability
- Robust and insensitive housing made of polyurethane
- Distillation time approx. 3 min per sample
- Detection limit 0.1 mg N
- Retrieval rate > 99.5%
- Reproducibility ± 1%
- Adjustable steam output (10% - 100%)
- Particularly easy, menu-driven operation using a single control (behr single-knob control)
- Programmable reaction time
- Programmable distillation time
- USB interface
- Level monitoring for the canister set
- Practical quick-release clamping device, which the user can also easily operate with their left hand

S 3

| Type | Product description | Art. No. |
|-----------|--|-----------|
| S 3 | Steam distiller, semi-automated | B00233703 |
| KAS 30 | Canister set for S 3, consisting of 3 canisters à 20 l, incl. float switches | B00218042 |
| KAS 30/10 | Canister set for S 3, consisting of 3 canisters à 10 l, incl. float switches | B00736342 |



S 3

Steam distiller S 4 with automatic addition of NaOH, H₂O and H₃BO₃ with automatic extraction of the sample residues and with 99 programs

- Exemplary safety and reliability
- Robust and insensitive housing made of polyurethane
- Distillation time approx. 3 min per sample
- Detection limit 0.1 mg N
- Retrieval rate > 99.5%
- Reproducibility ± 1%
- Adjustable steam output (10% - 100%)
- Particularly easy, menu-driven operation using a single control (behr single-knob control)
- Programmable reaction time
- Programmable distillation time
- USB interface
- Level monitoring for the canister set
- Practical quick-release clamping device, which the user can also easily operate with their left hand

S 4

| Type | Product description | Art. No. |
|-----------|--|-----------|
| S 4 | Steam distiller, fully automatic | B00218032 |
| KAS 40 | Canister set for S 4 and S 5, consisting of 4 canisters à 20 l, incl. float switches | B00218043 |
| KAS 40/10 | Canister set for S 4 and S 5, consisting of 4 canisters à 10 l, incl. float switches | B00513618 |



S 4



S 5

Steam distiller S 5 with automatic addition of NaOH, H₂O and H₃BO₃ with automatic extraction of the sample residues, with 99 programs and a connection option for external titrator

- Exemplary safety and reliability
- Robust and insensitive housing made of polyurethane
- Distillation time approx. 3 min per sample
- Detection limit 0.1 mg N
- Retrieval rate > 99.5%
- Reproducibility ± 1%
- Adjustable steam output (10% - 100%)
- Particularly easy, menu-driven operation using a single control (behr single-knob control)
- Programmable reaction time
- Programmable distillation time
- USB interface
- Level monitoring for the canister set
- Practical quick-release clamping device, which the user can also easily operate with their left hand

S 5

| Type | Product description | Art. No. |
|-----------|--|-----------|
| S 5 | Steam distiller, fully automatic, prepared for external titrator (e.g. TB 2) | B00218034 |
| KAS 40 | Canister set for S 4 and S 5, consisting of 4 canisters à 20 l, incl. float switches | B00218043 |
| KAS 40/10 | Canister set for S 4 and S 5, consisting of 4 canisters à 10 l, incl. float switches | B00513618 |
| TB 2 | Titration module for connection to the S 5 steam distilling apparatus, with Kjeldahl method and evaluation. Printer upon request | B00645403 |

Technical data for steam distillers

| | S 1 | S 2 | S 3 | S 4 | S 5 |
|-------------------------------------|---|---------------|---------------|-----------------|---------------|
| Voltage | 230 VAC/115 VAC | | | | |
| Frequency | 50/60 Hz | | | | |
| Power consumption | 1700 W | | | | |
| Current consumption | 9 A | | | | |
| Cooling water consumption | approx. 5 l/min | | | | |
| Distillation time | approx. 2 - 4 min per sample | | | | |
| Storage container | Any size required. Recommendation: behrotest® KAS canister sets | | | | |
| Interface | USB | | | | |
| Display | LCD | | | | |
| Programs | 1 | 1 | 10 | 99 | 99 |
| Dimensions (W x H x D in cm) | approx. 41 x 67.5 x 41 | | | | |
| Weight | approx. 20 kg | approx. 21 kg | approx. 23 kg | approx. 24,5 kg | approx. 29 kg |
| Titrator connection | no | no | no | no | yes |



Features of the various units

| | S 1 | S 2 | S 3 | S 4 | S 5 |
|--|-----|-----|-----|-----|-----|
| Automatic addition of H ₂ O | - | + | + | + | + |
| Automatic addition of NaOH | + | + | + | + | + |
| Automatic addition of H ₃ BO ₃ | - | - | - | + | + |
| Automatic extraction of the sample residues | - | - | + | + | + |
| Number of programs | 1 | 1 | 10 | 99 | 99 |
| Titration connection option | - | - | - | - | + |
| Programmable reaction time | | | + | | |
| Programmable distillation time | | | + | | |
| Automatic steam generation | | | + | | |
| Adjustable steam output (10% – 100%) | | | + | | |
| Separate purging program | | | + | | |
| Display language selectable by user | | | + | | |
| Optical error indications | | | + | | |
| Acoustic error indications | | | + | | |
| Door safety contact switch | | | + | | |
| USB interface | | | + | | |
| Standby mode between distillations | | | + | | |
| Level monitoring for the canister set | | | + | | |
| Different glass digestion tubes can be used | | | + | | |

Adapter for the use of different digestion vessels



Our practical adapter ensures that you can use digestion vessels by manufacturers, who deviate from standard sizes in our behrotest® steam distillers.

Adapter for the use of different digestion vessels

| Product description | Art.-No. |
|---|------------|
| Microadapter 100 ml PTFE for Micro-Kjeldahl vessels SR4 | B0023 2266 |
| PP-adapter for Büchi-vessels of S 1 - S 5 | B0023 2254 |


Canister sets

Behr canister sets are based on hazardous goods canisters with UN approval.

The level sensors form a unit with the screw caps. If necessary, the user can therefore also directly connect commercial chemical containers without any need for dangerous refilling or transfer actions.

Canister sets

| Type | Product description | Art. No. |
|-----------|--|-----------|
| KAS 20 | Canister set for S 1 and S 2, consisting of 2 canisters à 20 l, incl. float switches | B00218041 |
| KAS 20/10 | Canister set for S 1 and S 2, consisting of 2 canisters à 10 l, incl. float switches | B00704640 |
| KAS 30 | Canister set for S 3, consisting of 3 canisters à 20 l, incl. float switches | B00218042 |
| KAS 30/10 | Canister set for S 3, consisting of 3 canisters à 10 l, incl. float switches | B00736342 |
| KAS 40 | Canister set for S 4 and S 5, consisting of 4 canisters à 20 l, incl. float switches | B00218043 |
| KAS 40/10 | Canister set for S 4 and S 5, consisting of 4 canisters à 10 l, incl. float switches | B00513618 |



Canister with level sensor for waste disposal

Canister with level sensor for NaOH

Manual titration station STI

The STI manual titration station consists of:

- a burette with digital display and
- a magnetic stirrer with precise fitting holder for an Erlenmeyer flask

A screen serves as a neutral background and enables the user to precisely determine the colour alteration at the end of the titration. This means that the titrations are always performed under similar optical conditions. This improves the accuracy and reproducibility of the results.

The precise positioning of the vessel in the holder at the top of the magnetic stirrer also contributes towards this. The angular sides of the screen provide additional protection against lateral glare.

Manual titration station STI

| Type | Product description | Art. No. |
|------|---|-----------|
| STI | Manual titration system for the determination of nitrogen using the Kjeldahl method | B00218002 |
| TS | Tashiro mixed indicator, 1 l | B00491148 |

Technical data for the manual titration station STI

| | |
|-------------------------------------|----------------------|
| Voltage | 230 VAC |
| Frequency | 50/60 Hz |
| Weight | approx. 3.5 kg |
| Dimensions in cm (W x D x H) | approx. 33 x 20 x 60 |



STI



TS

behrotest® Dispenser



DOS 25

| Type | Product description | Art. No. |
|-----------|--|-----------|
| DOS 25 | behrotest® dispenser for metering sulfuric acid, 2.5-25 ml adjustable without bottle | B00661157 |
| LGF 2000 | behrotest® Laboratory bottle with ISO-Thread 2000 ml with graduation, crystal clear | B00225419 |
| LGFB 2000 | behrotest® Laboratory bottle with ISO-Thread 2000 ml with graduation, brown | B00225423 |



behr Labor



256211



behr Labor-Technik GmbH • Spangerstraße 8 • 40599 Düsseldorf/Germany
Tel.: (+49) (0) 211 – 7 48 47 17 • eMail: info@behr-labor.com
Internet: www.behr-labor.com

Subject to technical changes without notice. Errors and omissions excepted.



B00520182-EN - V3_1_017